

DATASHEET



	cryo:one	cryo:one⁺
System description	Pure electric unit for whole body cryotherapy with highly efficient engine	
Air temperature in chamber	down to -85°C	
Pre-cooling time approx.	50min	45min
Operating hours per day ¹	5	10
Number of cycles/hour	5	10
Drying mode	Adjustable and automatic at the end of the cooling period	
Dimensions entire system (BxTxH)	1200 x 1850 x 2470mm	1500 x 2150 x 2570mm
Dimensions interior (BxTxH)	900 x 900 x 2050mm	1200 x 1200 x 2050mm
Total weight	590kg	850kg
Voltage ²	380-400V/3/50Hz - 460V/3/60Hz	
Voltage range	340-440V@50Hz - 414-506V@60Hz	
Connected load	25A	32A
Recooling (optionally consumption-free with closed recooling system)	Water	
Water connection	G1" on top of the machine, flow temperature max. 30°C at min. 2 bar pressure	
Water consumption in litres/day ³	980	1550
Internet connection	LAN cable RJ45 on top of machine	

¹ The number of operation hours depend on the performed treatments cycles and can be restarted after drying cycle is complete.

² The voltage can be adjusted to almost any existing voltage with transformers. Please ask for further information.

³ The basis is the maximum operating time and number of therapies at 10°C water temperature. The actual water consumption depends on how the unit is used.

Available accessories	<p>Recooling package for consumption-free cooling</p> <p>Operation/music package consisting of Wlan-router, operation tablet 7" with additional app and holder, 2x headband with integrated Bluetooth headphones</p> <p>Cabinet housing of the machine in white coated wood</p>
Installation conditions	<p>Rel. air humidity max. 55%</p> <p>Air pressure 80 – 106kPa</p> <p>Temperature range 5 – 30°C</p>
Provided by the customer	<p>Necessary crane or lifting works</p> <p>Preparing the level installation site</p> <p>Installation of the water connection min. ¾" to the machine</p> <p>Installation of power and internet connection to the machine</p>

Set-up variants cryo:one *(cryo:one*)

